



# Dual-Band Antenna Series

## Model: AU-3G-AMPS

High performance GPS patch antenna with cutting-edge low noise amplifier. Low profile, waterproof, suction cup mounting



This **AU-3G-AMPS**, a member of our mobile antenna series coming up with dual-band features, is designed to simplify the need for an AVL or Fleet Management antenna systems. The combination of a high gain GPS antenna and a low profile and covert AMPS antenna is highly

ideal for those applications that requires durability, compact size, covert installation and ruggedized construction, such as covering vehicle roof and trunk lid interior deck or dashboard.

=====  
**Low Noise Figure/ Fully Weatherproof/ Ultra-high Sensitivity**  
**/Compact Construction/ Excellent Temperature Stability**  
=====

### Specifications:

	GPS Antenna	AMPS Antenna
<b>Features</b>	High performance GPS patch antenna with state-of-the-art low noise amplifier	AMPS 824~894 MHz
<b>Size</b>	64.5mm (D) x 13.6mm (H)	
<b>Frequency</b>	1575.42 MHz	824 MHz ~ 894 MHz
<b>Polarization</b>	RHCP (right hand circular polarization)	--

©2008 San Jose Technology, Inc. All specifications subject to change without notice.

<b>Gain</b>	26 dB typically	1.7 dBi
<b>Noise Figure</b>	1.2 max.	-----
<b>Attenuation</b>	20dB min. @ F0+/-50MHz	-----
<b>Band Width</b>	10 MHz	70 MHz for frequency of 824~894 MHz
<b>VSWR</b>	< 1.5	< 1.5
<b>Impedance</b>	50 ohm	50 ohm
<b>Power Supply</b>	Power Consumption: 2.7~5.5 VDC / 13 mA	Power Handling Capacity: 10 W
<b>Cable &amp; Connector</b>	3m RG-174 FME Connector	3m RG-174 SMA Connector
<b>Operating Temperature</b>	-40°C ~ +85°C	-40°C ~ +85°C
<b>Storage Temperature</b>	-45°C ~ +100°C	-45°C ~ +100°C

©2008 San Jose Technology, Inc.  
All specifications subject to change without notice.

Welcome custom design for GSM frequencies!